Appropriate embossing system

# **GRISOCOD**

### Small appliance with big impact Modular system for coding, rippling and cutting





Appropriate embossing system

### **GRISOCOD**

Designed for single- or double-sided coding of tubes with letter/figure codes (serial numbers, filling/expiry dates, etc.) on the fold of metal tubes or on the welded seam of plastic- or laminated tubes. Rippling jaws for the seals are also available. With a built-in cutting device any irregularities of the welded seam of plastic- or laminated tubes are neatly trimmed.

#### TWO DIFFERENT TYPES OF GRISOCOD ARE AVAILABLE

## GRISOCOD manual GRISOCOD pneumatic

**TECHNICAL DATA** 

Once the machine has been fitted with the required parts it is adjusted for height according to tube length. Filled tubes in single or multiple tube holders – in which they have already been closed – are placed between the jaws of the machine.

Coding and/or trimming are achieved by depressing a hand lever (GRISOCOD manual) resp. by actuating of the foot switch (GRISOCOD pneumatic). Correct positioning of each individual tube in the machine is ensured by a location peg which corresponds with holes in the tube holder.

Dimensions		• width	200mm				
		<ul><li>depth</li></ul>	300mm				
		<ul><li>height</li></ul>	420mm				
Weight		<ul><li>approx.</li></ul>	8kg manual / 11kg pneumatic				
Tube dimensions		Ø12mm until 60mm, length 20mm until 320mm					
Working width		• 90mm					
Script height		• 1.5mm standard; (2.0mm on request)					
Number of digits		• max. 12 (1.5mm) 9 (2.0mm)					
Marking jaws							
Accessories		flat jaw	marking jaw	marking/	rippling jaw	rippling jaw	cutting
				rippling jaw	1mm	3mm	device
Action	ArtNo.	A.130010	A.130020	A.130024	A.130025	A.130030	A.130040
Trimming		K 2x					K
Coding single-sided		K/M	K/M				
Coding double-sided			M 2x (K)				
Coding/Rippling		K	K				K
Coding/Rippling/Crimping				K (Set)			K
Coding/Rippling				M (Set)			
Crimping					K (pair)	M (pair)	
Crimping/Rippling					K (pair)		K
Key		M for metal tubes / K for plastic tubes					
Output		• up to 1'500 tubes per hour					
Accessories		multiple tube holder, Set with coding digits					

Special design on request (marking on two lines, Euroboring, special shaping of the weld seam by die cutting etc.)